



Sirius Optics
Unit 1
26 Darnick Street
Underwood, Qld 4119

Opening Hours
10am-5:30pm Mon-Fri
9am-2pm Sat

Phone: 07 3423 2355
www.sirius-optics.com.au

Swarovski CL Pocket 8x25 B Mountain Binoculars

AUD
\$1,090.00

Product Images



Short Description

The CL Pocket Mountain 8x25 are foldable compact binoculars of exceptional optical quality.

Description

FOR VIEWS THAT GO ON AND ON

CL Pocket Mountain binoculars equip you for every discovery. You will be thrilled with their small, foldable design that offers great optical quality, whether you are in the mountains, unexpectedly observing wildlife, or simply on your travels. Always at hand wherever you are.

CL Pocket Mountain 8x25 B

The CL Pocket Mountain 8x25 are foldable compact binoculars of exceptional optical quality. They offer optimum viewing comfort, even during long observation periods, and are easy to use. Even eyeglass wearers can fully benefit from the large field of view (357 ft/119 m) thanks to the individually adjustable twist-in eyecups.

Included

Field bag, carrying strap, raincover

Specifications

Technical Data

Magnification

8x

Effective objective lens diameter (mm)

25

Exit pupil diameter (in/mm)

0.12/3.1

Exit pupil distance (eye relief) (in/mm)

0.67/17

Field of view (ft/1000 yds / m/1000 m)

357/119

Field of view (degrees)

6.8

Field of view for eyeglass wearers (degrees)

6.8

Field of view, apparent (degrees)

52

Shortest focusing distance (ft/m)

8.2/2.5

Dioptic compensation (dpt)

± 5

Diopter correction at ∞ (dpt)

6

Light transmission (%)

88

Pupil distance (in/mm)

2.0-2.9/50-74

Twilight factor acc. to ISO 14132-1

14.2

Technical Data

Length approx. (in/mm)*

4.3/110

Width approx. (in/mm)**

3.9/98

Height approx. (in/mm)**

1.8/46

Weight approx. (oz/g)

12.2/345

Functional temperature

-13 °F to +131 °F (-25 °C / +55 °C)

Storage temperature

-22 °F to +158 °F (-30 °C / +70 °C)

Submersion tightness

13 ft / 4 m water depth (inert gas filling)

* Value with eyecups twisted in

** Dimensions at a pupil distance of 2.5 in / 64 mm