



Sirius Optics  
Unit 1  
26 Darnick Street  
Underwood, Qld 4119

Opening Hours  
10am-5:30pm Mon-Fri  
9am-2pm Sat

Phone: 07 3423 2355  
www.sirius-optics.com.au

## Swarovski ATX 30-70x115mm Angled Spotting Scope Set

**AUD**  
**\$7,490.00**

### Product Images



### Short Description

Taking functionality to a new level the ATX spotting scope system combines exceptionally flexible modularity with optical perfection.

Extreme detail recognition at crucial moments thanks to SWAROVISION technology and total ease of use ensure fascinating experiences in the great outdoors.

Phils Review : "Of all the spotting scopes used for birdwatching or hunting, this scope is the penultimate scope. Whether I have

been looking at wild western budgies around a desert waterhole in the late afternoon or sitting in a bush hide waiting for a flighty deer in low morning light, I have found this scope setup to be perfect for the job."

## Description

---

### ATX 30-70 x 115

The angled view significantly increases the comfort of long-term viewing, particularly when your subject is located in the sky, in a tree, or on a hill. The high limiting resolution of the 115-mm objective module allows you to make out the tiniest details. The largest lens aperture on the market for wildlife observation, excellent optical quality, and outstanding color vision make it an unbeatable spotting scope for use at dawn and dusk.

## Additional Information

---

Specifications	<b>Technical Data</b>
	Magnification
	30-70x
	Effective objective lens diameter (mm)
	115
	Exit pupil diameter (mm)
	3.9-1.6
	Eye relief (mm)
	20
	Field of view (ft/1000 yds / m/1000 m)
	104-57 ft / 35-19 m
	Field of view (degrees)
	1.98-1.09
	Field of view, apparent (degrees)
	57-71
	Shortest focusing distance (ft / m)
	15.7 ft / 4.8 m
	Diopter correction at $\infty$ (dpt)
	> 5
	Objective filter thread
	M 118 x 0.75
Focal length with TLS APO 30 mm (mm)	
900-2100	
Length (in / mm)	
17.3 / 440	
Weight (oz / g)	
102.6 / 2910	
Functional temperature	
-13 °F to +131 °F (-25 °C to +55 °C)	
Storage temperature	
-22 °F to +158 °F (-30 °C to +70 °C)	
Submersion tightness	
13 ft (4m) water depth (inert gas filling)	