



Sirius Optics
Unit 1
26 Darnick Street
Underwood, Qld 4119

Opening Hours
10am-5:30pm Mon-Fri
9am-2pm Sat

Phone: 07 3423 2355
www.sirius-optics.com.au

Swarovski CL Companion 8 X 30 Green - Northern Lights package

AUD
\$1,900.00

Product Images



Short Description

THE FREEDOM TO EXPERIENCE MORE

You'll never miss out with the new CL Companion. These elegant binoculars with impressive optics fit perfectly in your hand. They are always with you to ensure you make the most of every sighting.

CL Companion 8x30 B

The new CL Companion 8x30 has a 132 m (144 yd) field of view to give you the perfect overview. Its impressive optics with 8x magnification ensure your viewing is smooth and jitter-free. The ergonomic design of these compact, lightweight (490 g/17.2 oz) binoculars makes them an excellent companion providing you with unique experiences when you're on the move.

NORTHERN LIGHTS

As raw and rugged as northern landscapes. The NORTHERN LIGHTS accessory package features pure sheep's wool felt and sustainably produced leather. Made of 100% natural materials, this accessory package will protect your binoculars against the elements.

Technical Data

Magnification	8
Effective objective lens diameter (mm)	30
Exit pupil diameter (mm)	3.8
Exit pupil distance (eye relief) (mm)	16
Field of view (ft/1000 yds / m/1000 m)	396 / 132
Field of view (degrees)	7.6
Field of view for eyeglass wearers (degrees)	7.6
Field of view, apparent (degrees)	58
Shortest focusing distance (ft / m)	9.8 / 3
Dioptric compensation (dpt)	± 4
Diopter correction at ∞ (dpt)	>5
Light transmission (%)	90
Pupil distance (in/mm)	2.2-2.9 / 55-74
Twilight factor acc. to ISO 14132-1	15.5
Length approx. (in/mm)*	5.0 / 127
Width approx. (in/mm)**	4.5 / 118
Height approx. (in/mm)**	2.2 / 55
Weight approx. (oz/g)	17.3 / 490
Functional temperature	-13 °F to +131 °F (-25 °C / +55 °C)
Storage temperature	-22 °F to +158 °F (-30 °C / +70 °C)
Submersion tightness	13 ft / 4 m water depth (inert gas filling)

* Value with eyecups twisted in

** Dimensions at a pupil distance of 2.5 in / 64 mm

Specifications