



Sirius Optics
Unit 1
26 Darnick Street
Underwood, Qld 4119

Opening Hours
10am-5:30pm Mon-Fri
9am-2pm Sat

Phone: 07 3423 2355
www.sirius-optics.com.au

Swarovski SLC 10x56 Green III Binoculars

AUD
\$3,500.00

Product Images



Short Description

The new high-luminosity SLC 10x56 binoculars provide you with the benefit of the 10x magnification, so that you can make out details better. The optimized optical system for night use, combined with the outstanding edge-to-edge sharpness and a large field of view make observation easy for you even in poor light conditions. The extended depressions for improved grip and the balanced weight also ensure maximum comfort when using them.

THE EXPERIENCED EXPERT

Experiencing wildlife later in the day is particularly attractive for many people. This is precisely the time when otherwise very shy creatures, such as owls or even wildcats, make an appearance. The SLC 56 binoculars will provide you with maximum support as you make your eye-opening discoveries. They impress with their optimized optical system for night use and optimum viewing comfort that prevents any feeling of fatigue during observation.

SLC 10x56 W B

The new high-luminosity SLC 10x56 binoculars provide you with the benefit of the 10x magnification, so that you can make out details better. The optimized optical system for night use, combined with the outstanding edge-to-edge sharpness and a large field of view make observation easy for you even in poor light conditions. The extended depressions for improved grip and the balanced weight also ensure maximum comfort when using them.

Included

Field bag, eyepiece cover, objective lens cover and comfort carrying strap

Specifications

Magnification
10
Effective objective lens diameter (mm)
56
Exit pupil diameter (mm)
5.6
Exit pupil distance (eye relief) (mm)
19.5
Field of view (ft/1000 yds / m/1000 m)
330/110
Field of view (degrees)
6.3
Field of view for eyeglass wearers (degrees)
6.3
Field of view, apparent (degrees)
60
Shortest focusing distance (ft / m)
12.8/3.9
Dioptric compensation (dpt)
± 5
Diopter correction at ∞ (dpt)
8
Light transmission (%)
93
Pupil distance (in/mm)
2.2-3.0/56-76
Twilight factor acc. to ISO 14132-1
23.7

Technical Data

Length approx. (in/mm)*
7.56/192
Width approx. (in/mm)**
5.5/141
Height approx. (in/mm)**
2.87/73
Weight approx. (oz/g)
42.2/1195
Functional temperature
-13 °F to +131 °F (-25 °C / +55 °C)
Storage temperature
-22 °F to +158 °F (-30 °C / +70 °C)
Submersion tightness
13 ft / 4 m water depth (inert gas filling)