



Sirius Optics  
Unit 1  
26 Darnick Street  
Underwood, Qld 4119

Opening Hours  
10am-5:30pm Mon-Fri  
9am-2pm Sat

Phone: 07 3423 2355  
www.sirius-optics.com.au

## Swarovski SLC 15x56 WB Green III Binoculars

**AUD**  
**\$3,610.00**

### Product Images



### Short Description

The SLC 15x56 binoculars are the expert for observing over long distances. Their 15x magnification and optimized optics, combined with outstanding edge-to-edge sharpness allow you to see special moments, even over expansive areas. The extended depressions for improved grip and the balanced weight ensure maximum comfort when using them.

### Description

# THE EXPERIENCED EXPERT

Experiencing wildlife later in the day is particularly attractive for many people. This is precisely the time when otherwise very shy creatures, such as owls or even wildcats, make an appearance. The SLC 56 binoculars will provide you with maximum support as you make your eye-opening discoveries. They impress with their optimized optical system for night use and optimum viewing comfort that prevents any feeling of fatigue during observation.

## Included

Field bag, eyepiece cover, objective lens cover and comfort carrying strap

## Additional Information

### Specifications

Magnification  
15  
Effective objective lens diameter (mm)  
56  
Exit pupil diameter (mm)  
3.7  
Exit pupil distance (eye relief) (mm)  
16  
Field of view (ft/1000 yds / m/1000 m)  
234/78  
Field of view (degrees)  
4.5  
Field of view for eyeglass wearers (degrees)  
4.5  
Field of view, apparent (degrees)  
62  
Shortest focusing distance (ft / m)  
12.8/3.9  
Dioptric compensation (dpt)  
± 5  
Diopter correction at ∞ (dpt)  
8  
Light transmission (%)  
93  
Pupil distance (in/mm)  
2.2-3.0/56-76  
Twilight factor acc. to ISO 14132-1  
29

### Technical Data

Length approx. (in/mm)\*  
7.56/192  
Width approx. (in/mm)\*\*  
5.5/141  
Height approx. (in/mm)\*\*  
2.87/73  
Weight approx. (oz/g)  
42.3/1200  
Functional temperature  
-13 °F to +131 °F (-25 °C / +55 °C)  
Storage temperature  
-22 °F to +158 °F (-30 °C / +70 °C)  
Submersion tightness  
13 ft / 4 m water depth (inert gas filling)