



Sirius Optics
Unit 1
26 Darnick Street
Underwood, Qld 4119

Opening Hours
10am-5:30pm Mon-Fri
9am-2pm Sat

Phone: 07 3423 2355
www.sirius-optics.com.au

Swarovski SLC 8x56 WB Green III Binoculars

AUD
\$3,420.00

Product Images



Short Description

SLC 8x56 W B

With the high-luminosity SLC 8x56 model, you will benefit from binoculars that offer exceptionally high transmission and you will be thrilled by their optics that have been optimized for night use, with outstanding edge-to-edge sharpness and a large field of view. The extended depressions for improved grip and the balanced weight ensure maximum comfort when using them.

THE EXPERIENCED EXPERT

Experiencing wildlife later in the day is particularly attractive for many people. This is precisely the time when otherwise very shy creatures, such as owls or even wildcats, make an appearance. The SLC 56 binoculars will provide you with maximum support as you make your eye-opening discoveries. They impress with their optimized optical system for night use and optimum viewing comfort that prevents any feeling of fatigue during observation.

SWAROCLEAN

The SWAROCLEAN anti-adhesive coating ensures that the external surfaces of the lenses are clean.

SLC 8x56 W B

With the high-luminosity SLC 8x56 model, you will benefit from binoculars that offer exceptionally high transmission and you will be thrilled by their optics that have been optimized for night use, with outstanding edge-to-edge sharpness and a large field of view. The extended depressions for improved grip and the balanced weight ensure maximum comfort when using them.

Included

Field bag, eyepiece cover, objective lens cover and comfort carrying strap

Additional Information

Specifications

| | |
|--|---|
| Magnification | 8 |
| Effective objective lens diameter (mm) | 56 |
| Exit pupil diameter (mm) | 7 |
| Exit pupil distance (eye relief) (mm) | 23 |
| Field of view (ft/1000 yds / m/1000 m) | 400/133 |
| Field of view (degrees) | 7.6 |
| Field of view for eyeglass wearers (degrees) | 7.6 |
| Field of view, apparent (degrees) | 60 |
| Shortest focusing distance (ft / m) | 12.8/3.9 |
| Dioptric compensation (dpt) | ± 4 |
| Diopter correction at ∞ (dpt) | 5 |
| Light transmission (%) | 93 |
| Pupil distance (in/mm) | 2.2-3.0/56-76 |
| Twilight factor acc. to ISO 14132-1 | 21.2 |
| Length approx. (in/mm)* | 7.64/194 |
| Width approx. (in/mm)** | 5.5/141 |
| Height approx. (in/mm)** | 2.87/73 |
| Weight approx. (oz/g) | 43.2/1225 |
| Functional temperature | -13 °F to +131 °F (-25 °C / +55 °C) |
| Storage temperature | -22 °F to +158 °F (-30 °C / +70 °C) |
| Submersion tightness | 13 ft / 4 m water depth (inert gas filling) |

* Value with eyecups twisted in

** Dimensions at a pupil distance of 2.5 in / 64 mm